

**KEY NOTES**


- 07 EXTERIOR EQUIPMENT PAD FOR CHILLER AND TRANSFORMER. REFERENCE TYPICAL DETAIL ON THIS SHEET.
- 15 PROVIDE 4 FOOT HEEL AND REINFORCE ACCORDING TO SHORTEST WALL ON SITE RETAINING WALL SCHEDULE WITH (6) #5 LONGITUDINAL FOOTING REINFORCEMENT TOP AND BOTTOM. TYPICAL REINFORCEMENT THEREAFTER.
- 16 PROVIDE 3 FOOT HEEL AND REINFORCE ACCORDING TO SHORTEST WALL ON SITE RETAINING WALL SCHEDULE WITH (5) #5 LONGITUDINAL FOOTING REINFORCEMENT TOP AND BOTTOM. TYPICAL REINFORCEMENT THEREAFTER.
- 37 AT WF3 BACKFILL WALL EVENLY ON BOTH SIDES.

**FOUNDATION PLAN NOTES**


- A. REFERENCE ARCHITECTURAL DRAWINGS FOR DIMENSIONS TO NONBEARING WALLS, WALL CONTROL JOINTS AND OPENINGS.
- B. ALL ELEVATIONS ARE BASED ON A REFERENCED FIRST FLOOR ELEVATION OF 0'-0" = 316.64' AND REFERENCED GROUND FLOOR ELEVATION OF -15'-4" = 301.30'. REFER TO ARCHITECTURAL DRAWINGS FOR FINISH FLOOR MATERIALS.
- C. TOP OF ALL COLUMN AND WALL FOOTINGS MUST BE AT THE FOLLOWING ELEVATIONS UNLESS OTHERWISE NOTED ON PLAN. EXTERIOR WALL AND COLUMN FOOTINGS -2'-0" (-2'-0" AT FIRST FLOOR SLAB ON GRADE. (-17'-4" AT GROUND FLOOR). INTERIOR WALL FOOTINGS -0'-8" (-0'-8" AT FIRST FLOOR SLAB ON GRADE. -16'-0" AT GROUND FLOOR).
- D. NOT ALL UTILITY LOCATIONS ARE SHOWN ON PLAN. THE CONTRACTOR MUST COORDINATE THE LOCATIONS, SIZES, AND INVERTS OF UTILITIES. AT LOCATIONS WHERE UTILITIES PASS BELOW THE TOP OF FOOTING ELEVATION, STEP THE TOP OF FOOTING DOWN ON EACH SIDE PER THE "STEPPED FOOTING DETAIL" AND SLEEVE THE UTILITY THROUGH THE FOUNDATION WALL. THE CONTRACTOR MAY, AT HIS/HER OPTION, SLEEVE THE UTILITY THROUGH THE FOUNDATION PER THE "UTILITY SLEEVE DETAIL".
- E. UNLESS OTHERWISE INDICATED, EXTEND WALL FOOTINGS A MINIMUM OF 6 INCHES BEYOND ENDS OF WALLS.
- F. NOT ALL SITE WALLS ARE NOT SHOWN ON PLAN. CONTRACTOR MUST COORDINATE CIVIL AND LANDSCAPE DRAWINGS FOR SITE WALL INFORMATION.
- G. DIMENSIONS SHOWN ON FOUNDATION PLAN ARE TO COLUMN GRIDLINES AND OUTSIDE FACE OF FOUNDATION WALLS, UNLESS OTHERWISE NOTED.

**FRAMING PLAN NOTES**

- A. REFERENCE FOUNDATION PLAN AND ARCHITECTURAL DRAWINGS FOR DIMENSIONS NOT SHOWN.
- B. TOP OF FINISHED FLOOR ELEVATION SHALL BE AS NOTED ON SLAB PLANS.
- C. FLOOR JOISTS AND BEAMS MUST BE EQUALLY SPACED BETWEEN POINTS OF KNOWN DIMENSIONS (NOT TO EXCEED 4'-0" ON-CENTER).
- D. STEEL ROOF FRAMING SUPPORTING 1 1/2" STEEL ROOF DECK MUST BE EQUALLY SPACED BETWEEN POINTS OF KNOWN DIMENSIONS (NOT TO EXCEED 5'-0" ON-CENTER).
- E. CONTRACTOR MUST POUR SLAB TO THICKNESS. SLAB AND JOISTS ARE NOT DESIGNED FOR EXCESS IN THICKNESS DUE TO CONCRETE POUR PONDING.
- F. PROVIDE BOTTOM CHORD EXTENSIONS AT ALL JOISTS ON COLUMN CENTERLINES.
- G. AT STEEL ROOF FRAMING, BOTTOM OF DECK ELEVATIONS ARE SHOWN ON PLAN. INTERMEDIATE ELEVATIONS SHALL BE STRAIGHT LINES BETWEEN GIVEN ELEVATIONS. INTERPOLATE AS REQUIRED FOR INTERMEDIATE BEARING ELEVATIONS, UNLESS OTHERWISE NOTED.
- H. COORDINATE AND VERIFY ALL MEMBER LOCATIONS, DIMENSIONS, WEIGHTS, OPENING SIZES, AND CURB DIMENSIONS FOR ALL MECHANICAL EQUIPMENT WITH THE ACTUAL EQUIPMENT FURNISHED. INCLUDE THIS INFORMATION ON THE JOIST AND STRUCTURAL STEEL SHOP DRAWINGS.




**4 TYPICAL CONCRETE WALL VERTICAL JOINT DETAILS**  
NTS




MAX RETAINED HEIGHT	FOOTING DIMENSIONS		FOOTING T&B REINFORCING		KEY DIMENSIONS		KEY REINFORCING		WALL DIMENSIONS			WALL REINFORCING		
	T	H	DEPTH	LONGITUDINAL	TRANSVERSE	WIDTH	DEPTH	VERT & HORIZ	RETAINING FACE VERT	WALL WIDTH	RETAINING FACE VERT	NON-RETAINING FACE VERT	HORIZONTAL	
4'-0"	1'-0"	5'-0"	1'-0"	(7) #5	#5 AT 12" OC	0'-8"	1'-0"	#5 AT 12" OC EW	0'-8"	#4 AT 12" OC - CTRD ON WALL	-	-	#4 AT 12" OC	
6'-0"	1'-0"	6'-6"	1'-2"	(8) #5	#5 AT 12" OC	0'-8"	1'-0"	#5 AT 12" OC EW	0'-8"	#5 AT 12" OC - CTRD ON WALL	-	-	#5 AT 12" OC - CTRD ON WALL	
8'-0"	1'-6"	8'-4"	1'-2"	(9) #5	#5 AT 12" OC	0'-10"	1'-0"	#5 AT 14" OC EW	0'-10"	#5 AT 14" OC	#5 AT 14" OC	-	#5 AT 12" OC - CTRD ON WALL	
12'-0"	1'-6"	10'-0"	1'-6"	(13) #6	#6 AT 12" OC	0'-10"	1'-6"	#5 AT 12" OC EW	0'-10"	#7 AT 12" OC	#5 AT 12" OC	-	#5 AT 12" OC	
16'-0"	2'-0"	13'-6"	1'-8"	(17) #6	#6 AT 12" OC	1'-0"	1'-8"	#5 AT 12" OC EW	1'-0"	#7 AT 6" OC	#5 AT 16" OC AT SITE WALL #7 AT 12" OC BLDG BASEMENT	-	#5 AT 12" OC	
18'-0"	2'-0"	17'-0"	1'-8"	(20) #6	#6 AT 12" OC	1'-2"	2'-0"	#5 AT 12" OC EW	1'-2"	#8 AT 6" OC	#5 AT 6" OC	-	#5 AT 12" OC	

**2 TYPICAL SITE AND BUILDING RETAINING WALL SCHEDULE AND DETAIL**  
NTS



**3 TYPICAL EXTERIOR EQUIPMENT PAD DETAIL**  
NTS



**1 MECHANICAL ENCLOSURE PLAN**  
3/16" = 1'-0"

**COOPER ACADEMY**  
A & R  
PROJECT TITLE



02/26/2024

**lynchmykins**  
STRUCTURAL ENGINEERS

301 N West St., Suite 105  
Raleigh, NC 27603  
919.782.1832 - lynchmykins.com  
LM Project Number: LK21.298  
Corporation No. C-4360

1. THIS DRAWING IS THE PROPERTY AND BOOMERANG DESIGN P.L. AND IS NOT TO BE REPRODUCED OR COPIED IN WHOLE OR IN PART. IF IT IS NOT TO BE USED ON ANY OTHER PROJECT AND IS TO BE RETURNED ON REQUEST.

2. MATERIALS, DIMENSIONS AND ALL OTHER CONDITIONS WHICH ARE NOT OTHERWISE SPECIFIED ON THIS DRAWING SHALL BE CONTROLLED BY HAVING THE SAME MEANING AS EARLIER INDICATED CONDITIONS WHICH ARE MORE FULLY DEFINED ELSEWHERE ON THIS PROJECT OR OTHER DRAWINGS OF THIS PROJECT.

3. DO NOT SCALE OFF DIMENSIONS.

NO.	DATE	DESCRIPTION
1	2/26/2024	ADDENDUM 2

**CD**  
PERMIT SET  
**2307**  
BOOMERANG DESIGN PROJECT NUMBER  
**02.26.2024**  
DRAWING RELEASE DATE

**ENLARGED PLANS**  
SHEET TITLE

**S401**

SHEET