

① MAIN ELECTRICAL ROOM PART PLAN  
1/2" = 1'-0"

CLIENT AND PROJECT



DURHAM TECH  
COMMUNITY  
COLLEGE

**LIFE SCIENCES  
BUILDING**

1650 E Lawson St.  
Durham, NC 27703

SCO ID: 23-26245-02B  
NCCCS ID: 2731

DESIGNER



PO BOX 14637  
RALEIGH, NORTH CAROLINA 27620  
TELEPHONE: 919.661.6935  
MAIL: info@andrejohnsonarchitect.com

© 2024 Andre Johnson Architect, PLLC  
Duplication or reproduction by any means without  
the express written consent of Andre Johnson  
Architect is a violation of Federal and international  
law. The information contained on this document is  
the intellectual property of Andre Johnson Architect  
and all rights thereto are Reserved. For exceptions,  
refer to the Owner Architect Agreement.



PO BOX 12037  
RESEARCH TRIANGLE PARK  
NORTH CAROLINA 27709  
TELEPHONE: 919.941.9000  
www.obrienatkins.com

CONSULTANT AND REGISTRATION

**LORING**  
CONSULTING ENGINEERS

Loring Consulting Engineers, Inc.  
1007 Slater Road, Suite 210  
Durham, NC 27713  
P: 919.355.5000  
www.loringengineers.com  
New York City • Washington, DC • Princeton • Durham • Toronto

REGISTRATION



05-07-2025

ISSUE

No.	Date	Description
-----	------	-------------

SHEET INFO

**EARLY PACKAGE  
ELECTRICAL  
PART PLANS**

**EP-E300**

PROJECT NO: 13774-000

DATE: 05/07/2025

EARLY EQUIPMENT PACKAGE



DURHAM TECH  
COMMUNITY  
COLLEGE

LIFE SCIENCES  
BUILDING

1650 E Lawson St.  
Durham, NC 27703

SCO ID: 23-26245-02B  
NCCCS ID: 2731

DESIGNER



PO BOX 14637  
RALEIGH, NORTH CAROLINA 27620  
TELEPHONE: 919.661.6935  
MAIL: info@andjohnsonarchitect.com

© 2024 Andre Johnson Architect, PLLC  
Duplication or reproduction by any means without  
the express written consent of Andre Johnson  
Architect is a violation of Federal and international  
law. The information contained on this document is the  
intellectual property of Andre Johnson Architect  
and all rights thereto are Reserved. For exceptions,  
refer to the Owner/Architect Agreement.



PO BOX 12037  
RESEARCH TRIANGLE PARK  
NORTH CAROLINA 27709  
TELEPHONE: 919.941.9000  
www.obrienatkins.com

CONSULTANT AND REGISTRATION

LORING  
CONSULTING ENGINEERS

Loring Consulting Engineers, Inc.  
1007 Slater Road, Suite 210  
Durham, NC 27703  
P: 919.355.5000  
www.loringengineers.com  
New York City • Washington, DC • Princeton • Durham • Toronto

REGISTRATION



NC LICENSE: C-3302



05-07-2025

ISSUE

No. Date Description


SHEET INFO

EARLY PACKAGE  
ELECTRICAL  
SINGLE LINE  
DIAGRAM

































































EP-E401

PROJECT NO: 13774-000  
DATE: 05/07/2025  
EARLY EQUIPMENT PACKAGE

LOCATION: MAIN ELECTRICAL 207				REMARKS:		PANEL DESIGNATION:  <b>MSB-1</b>
SERVICE:	480/277	V	3	- PHASE		
MAINS:	3000	A MCB	4	- WIRE		
MOUNTING: FLOOR						
NEUTRAL:	Yes			GROUNDING:	Yes	
				GROUND BUS:	Yes	
				A/C RATING:	100K	
CKT #	TYPE	SWITCH FRAME (AMP)	POLES	FUSE / TRIP (AMP)	FEEDER	SERVICE
1	CB	800 A	3	800 A	2 SETS OF (4-500kcmil, 1#1/0G, ...)	DISTRIBUTION PANEL DP-1
2	CB	1200 A	3	1000 A	3 SETS OF (4-500kcmil, 1#2/0G, ...)	DISTRIBUTION PANEL DP-2A
3	CB	1200 A	3	1000 A	3 SETS OF (4-500kcmil, 1#2/0G, ...)	DISTRIBUTION PANEL DP-2B
4	CB	250 A	3	225 A	3#4/0, 1#4G, 2-1/2"IC	PANEL EV (VIA XFMR)
5	--	--	3	--	--	SPACE
6	--	--	3	--	--	SPACE
Load Classification				Connected Load	Demand Factor	Estimated Demand
Motor				19.51 kVA	100.00%	19.51 kVA
Other				131.52 kVA	100.00%	131.52 kVA
Lighting				19.26 kVA	100.00%	19.26 kVA
Kitchen Equipment				41.18 kVA	65.00%	26.77 kVA
HVAC				875.63 kVA	100.00%	875.63 kVA
Receptacle				495.04 kVA	51.01%	252.52 kVA
				TOTAL CONNECTED LOAD:		1547.16 kVA
				DEMAND FACTOR:		84.30%
				TOTAL DEMAND LOAD:		1304.24 kVA
				TOTAL DEMAND X 1.25 SPARE:		1630.30 kVA
				AMPERE AT ( 480 V):		1961 A





	SYMBOLS		PIPING, VALVES AND GAUGES	
		FIRE DAMPER (FD) W/ ACCESS DOOR		GLOBE VALVE
		DUCT SIZE (FIRST FIGURE INDICATES PLAN SIZE)		GATE VALVE
		SUPPLY DUCT UP (DISCHARGE SIDE OF FAN)		CHECK VALVE
		SUPPLY DUCT DOWN (DISCHARGE SIDE OF FAN)		AUTOMATIC TWO-WAY CONTROL VALVE
		RETURN OR EXHAUST DUCT UP (SUCTION SIDE OF FAN)		BALL VALVE
		RETURN OR EXHAUST DUCT DOWN (SUCTION SIDE OF FAN)		THERMOMETER
		ACOUSTIC LINING IN DUCT		PRESSURE GAUGE, GAUGE COCK
		FLEXIBLE CONNECTION		MANUAL AIR VENT
		ELBOW WITH TURNING VANES		AUTOMATIC AIR VENT
		RADIUS ELBOW		ARROW INDICATES DIRECTION OF FLOW
		VOLUME DAMPER W/DUCT ACCESS DOOR		UNION
		VARIABLE AIR VOLUME TERMINAL UNIT		CAPPED PIPE
		MOTORIZED DAMPER W/DUCT ACCESS DOOR		"Y" TYPE STRAINER WITH CAPPED BLOWDOWN VALVE
		ACCESS DOOR IN DUCT		ELBOW TURNED UP
		SLOPING RISE IN DUCT IN DIRECTION OF ARROW		ELBOW TURNED DOWN
		SLOPING DROP IN DUCT IN DIRECTION OF ARROW		TEE DOWN CONNECTION
		SUPPLY DIFFUSER		TEE UP CONNECTION
		SUPPLY DIFFUSER - 3 WAY, 2 WAY, 1 WAY		
		LINEAR SUPPLY DIFFUSER		
		ACOUSTICAL LINING		
		SPIRAL DOUBLE WALL WITH INSULATION		
		NEW WORK		
		THERMOSTAT		
		OCCUPANCY COUNTER		
		POINT OF NEW CONNECTION TO EXISTING WORK		
		POINT OF DISCONNECTION		
		SMOKE DETECTOR		
		STATIC PRESSURE SENSOR		
		AIR MEASURING DEVICE/AIR FLOW STATION		
		TEMPERATURE TRANSMITTER SENSOR		
		RETURN AIR GRILLE		
		EXISTING WORK TO BE REMOVED		
		EXISTING WORK TO REMAIN		
		REFRIGERANT LINE SUPPLY		
		REFRIGERANT LINE RETURN		
		CONDENSER WATER SUPPLY		
		CONDENSER WATER RETURN		
		CHILLED WATER SUPPLY		
		CHILLED WATER RETURN		
		HOT WATER SUPPLY		
		HOT WATER RETURN		
		NATURAL GAS SUPPLY		
		NATURAL GAS RETURN		
		WIRE MESH SCREEN		
		WALL TRANSFER GRILLE		
		AREA NOT IN SCOPE OF WORK		
		FLEX DUCT		

MECHANICAL ABBREVIATIONS			
AD	ACCESS DOOR	LE	LAB EXHAUST
AFF	ABOVE FINISHED FLOOR	LD	LINEAR DIFFUSER
AL	ACOUSTICAL LINING	LPS	LOW PRESSURE STEAM
AHU	AIR HANDLING UNIT	LPR	LOW PRESSURE STEAM CONDENSATE RETURN
BG	BOTTOM GRILLE	MBH	THOUSAND BTUS PER HOUR
BN	BOTTOM NECK	NK	NECK (AS RELATED TO DUCT & DIFFUSER)
CAV	CONSTANT AIR VOLUME	NIC	NOT IN THIS CONTRACT
CB	CHILLED BEAM	NTS	NOT TO SCALE
CC	COOLING COIL	NC	NORMALLY CLOSED
CD	CEILING DIFFUSER	NO	NORMALLY OPEN
CG	CEILING GRILLE	OAD	OUTSIDE AIR DAMPER
CHW	CHILLED WATER	OAI	OUTSIDE AIR INTAKE
COD	CLEAN OUT DOOR	OED	OPEN END DUCT WITH WMS
CR	CEILING REGISTER	RA	RETURN AIR
CFM	CUBIC FEET OF AIR PER MINUTE	RHC	REHEAT COIL
CUH	CABINET UNIT HEATER	RTU	ROOFTOP UNIT
DSD	DUCT MOUNTED SMOKE DETECTOR	SD	SMOKE DAMPER AND ACCESS DOOR
EDH	ELECTRIC DUCT HEATER	SPD	FIRE SMOKE DAMPER USED FOR SMOKE PURGE
ELH	ELECTRIC UNIT HEATER	SMUA	MAKE UP AIR FOR SMOKE PURGE SYSTEM
EA	EXHAUST AIR	SPX	SMOKE PURGE EXHAUST AIR
EL	ELEVATION	ST	SOUND ATTENUATOR
FD	FIRE DAMPER AND ACCESS DOOR	SX	SMOKE EXHAUST
FSD	FIRE SMOKE DAMPER AND ACCESS DOOR	SWEH	SIDE WALL ELECTRIC HEATER
FC	FLEXIBLE CONNECTION	TX	TOILET EXHAUST
FOD	FLAT OVAL DUCT	TW	THERMOMETER WELL
FOS&R	FUEL OIL SUPPLY AND RETURN	TD	TRANSFER DUCT
GPM	GALLONS PER MINUTE	TO	TRANSFER OPENING
GW	GLYCOL WATER	TG	TOP GRILLE
GX	GENERAL EXHAUST	TR	TOP REGISTER
HC	HEATING COIL	TRG	TRANSFER GRILLE
HV	HEATING AND VENTILATING UNIT	TRR	TRANSFER REGISTER
HWR	HOT WATER RETURN	TN	TOP NECK
HWS	HOT WATER SUPPLY	UH	UNIT HEATER
KE	KILN EXHAUST	VAV	VARIABLE AIR VOLUME
KX	KITCHEN EXHAUST	WMS	WIRE MESH SCREEN

MECHANICAL GENERAL NOTES	
1.	DESIGN DRAWINGS ARE TO BE CONSIDERED DIAGRAMMATIC. OFFSETS MAY BE REQUIRED TO AVOID EXISTING SERVICES, OTHER TRADES, ETC. COORDINATE WORK WITH ALL TRADES AND FIELD CONDITIONS
2.	CX SERVICES TO BE RETAINED BY DTCC
3.	ALL LAB EXHAUST DUCTS SHALL BE CONSTRUCTED OF APPROVED G90 GALVANIZED SHEET STEEL WITH MINIMUM 14 GAGE (0.079 INCHES THICKNESS), UNLESS OTHERWISE SPECIFIED. ALL FUME HOOD EXHAUST DUCTWORK SHALL BE MINIMUM 18 GAUGE WELDED STAINLESS STEEL FROM THE FUME HOOD TO THE MAIN EXHAUST DUCT
4.	LOCATIONS OF NEW UTILITIES ARE GENERALLY SCHEMATIC. CONTRACTOR SHALL COORDINATE ALL NEW UTILITIES, SERVICES, ETC. WITH EXISTING STRUCTURAL AND ARCHITECTURAL DRAWINGS AND PROVIDE ALL OFFSETS AS REQUIRED
5.	CONTRACTOR IS RESPONSIBLE FOR MAINTAINING AND RESTORING THE CONTINUITY OF ALL EXISTING SYSTEMS AFFECTED, INCLUDING BUT NOT LIMITED TO: INSULATION, VAPOR BARRIER, VALVES, CAPS, ETC
6.	SUBMIT SHOP DRAWINGS OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES OR ITEMS ORDERED
7.	COORDINATE ALL EQUIPMENT REQUIREMENTS WITH APPROPRIATE TRADES (I.E., CONDENSATE PUMPS COORDINATED WITH ELECTRICAL, PLUMBING, ATC, ETC.)
8.	VERIFY AND COORDINATE ALL EQUIPMENT ACCESS AND CLEARANCES WITH THE ARCHITECT, GENERAL CONTRACTOR, AND/OR CONSTRUCTION MANAGER.
9.	LOCATE ALL DUCT VOLUME DAMPERS ABOVE ACCESSIBLE LOCATIONS. PROVIDE REMOTE CABLE OPERATED VOLUME DAMPERS WITH THE OPERATOR ACCESSIBLE VIA THE AIR OUTLET WHEN BRANCH DUCTWORK IS LOCATED WITHIN AN INACCESSIBLE LOCATION
10.	ALL EXPOSED DUCTWORK SHALL BE INTERNALLY LINED, SEE SPECIFICATIONS
11.	CONTRACTOR SHALL BE RESPONSIBLE FOR THE WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF SAME WHICH MAY BE DAMAGED, LOST OR STOLEN WITHOUT ADDITIONAL COST TO OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING OR REPAIRING ANY BUILDING SYSTEM THAT SERVES OTHER AREAS THAT ARE DAMAGED OR IMPROPERLY MOVED AS A RESULT OF THE WORK.
12.	BALANCE ALL AIR OUTLETS TO THE CFM INDICATED ON THE PLANS
13.	ALL CONNECTIONS TO SUPPLY DUCTS AND CEILING DIFFUSERS SHALL BE AIR TIGHT AND SEALED WITH WATER BASED SEALANT
14.	ALL DUCT SIZES NOTED INDICATE THE CLEAR INSIDE DIMENSIONS OF DUCTWORK. SHEET METAL DIMENSIONS SHALL BE INCREASED WHERE DUCTWORK IS LINED INTERNALLY
15.	PROVIDE ALL REMOVABLE ACCESS TILES IN HUNG CEILING FOR ACCESS TO ALL VOLUME AND FIRE DAMPERS (EXISTING OR NEW) AND ALL OTHER MECHANICAL AND ELECTRICAL EQUIPMENT REQUIRING ACCESS FOR MAINTENANCE AND ADJUSTMENTS
16.	LOCATE THERMOSTATS AS REQUIRED AND DICTATED BY THE CONSTRUCTION CONDITIONS
17.	ALL SUPPLY, RETURN, AND EXHAUST DUCTWORK SHALL BE INSULATED THROUGHOUT. ALL DUCTWORK LOCATED OUTDOORS, ON ROOF SHALL BE INSULATED AND FURTHER WEATHERPROOFED WITH JACKETING

MECHANICAL CODES AND STANDARDS	
DESIGN AND PERFORMANCE OF COMPONENTS AND METHODS SPECIFIED HEREIN SHALL COMPLY WITH THE APPLICABLE PROVISIONS OF THE CODES, STANDARDS, AND MANUFACTURER'S RECOMMENDATIONS OF THE ENTITIES LISTED BELOW.	
1) BUILDING	FACILITY MANAGEMENT STANDARDS FOR ALTERATIONS AND CONSTRUCTION
2) BC	2018 NORTH CAROLINA BUILDING CODE
3) MC	2018 NORTH CAROLINA MECHANICAL CODE
4) ECC	2018 NORTH CAROLINA ENERGY CONSERVATION CODE
5) ASHRAE	AMERICAN SOCIETY OF HEATING, REFRIGERATION AND AIR CONDITIONING ENGINEERS
6) ASTM	AMERICAN SOCIETY FOR TESTING MATERIALS
7) ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
8) UL	UNDERWRITERS LABORATORIES, INC
9) FM	FACTORY MUTUAL
10) NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
11) SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTOR'S NATIONAL ASSOCIATION
12) ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS
13) AMCA	AIR MOVING AND CONDITIONING ASSOCIATION
14) ARI	AMERICAN REFRIGERATION INSTITUTE
15) MSS	MANUFACTURER'S STANDARDIZATION SOCIETY OF THE VALVE AND FITTING INDUSTRY.

MECHANICAL	
SUMMARY	MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT
THERMAL ZONE	
ZONE	4A
WINTER DRY BULB:	16°F
SUMMER DRY BULB:	93°F
INTERIOR DESIGN CONDITIONS	
WINTER DRY BULB:	70°F +/- 3°F
SUMMER DRY BULB:	74°F +/- 3°F
COOLING RELATIVE HUMIDITY:	50% +/- 15%
HEATING RELATIVE HUMIDITY:	N/A
BUILDING HEATING LOAD:	947.4 MBH
BUILDING COOLING LOAD:	3311.4 MBH
MECHANICAL SPACING CONDITIONING SYSTEM	
UNITARY	
DESCRIPTION OF UNIT:	DX COOLED HEAT PUMPS WITH ELECTRIC REHEAT VAV
HEATING EFFICIENCY:	SEE EQUIPMENT SCHEDULES OR EXISTING
COOLING EFFICIENCY:	SEE EQUIPMENT SCHEDULES OR EXISTING
SIZE CATEGORY OF UNIT:	SEE EQUIPMENT SCHEDULES OR EXISTING
BOILER	
SIZE CATEGORY. IF OVERSIZED, STATE REASON.:	N/A
CHILLER	
SIZE CATEGORY. IF OVERSIZED, STATE REASON.:	N/A
LIST EQUIPMENT EFFICIENCIES:	(SEE EQUIPMENT SCHEDULES)

MECHANICAL GENERAL NOTES		
1.	DESIGN DRAWINGS ARE TO BE CONSIDERED DIAGRAMMATIC. OFFSETS MAY BE REQUIRED TO AVOID EXISTING SERVICES, OTHER TRADES, ETC. COORDINATE WORK WITH ALL TRADES AND FIELD CONDITIONS	
2.	CX SERVICES TO BE RETAINED BY DTCC	
3.	ALL LAB EXHAUST DUCTS SHALL BE CONSTRUCTED OF APPROVED G90 GALVANIZED SHEET STEEL WITH MINIMUM 14 GAGE (0.079 INCHES THICKNESS), UNLESS OTHERWISE SPECIFIED. ALL FUME HOOD EXHAUST DUCTWORK SHALL BE MINIMUM 18 GAUGE WELDED STAINLESS STEEL FROM THE FUME HOOD TO THE MAIN EXHAUST DUCT	
4.	LOCATIONS OF NEW UTILITIES ARE GENERALLY SCHEMATIC. CONTRACTOR SHALL COORDINATE ALL NEW UTILITIES, SERVICES, ETC. WITH EXISTING STRUCTURAL AND ARCHITECTURAL DRAWINGS AND PROVIDE ALL OFFSETS AS REQUIRED	
5.	CONTRACTOR IS RESPONSIBLE FOR MAINTAINING AND RESTORING THE CONTINUITY OF ALL EXISTING SYSTEMS AFFECTED, INCLUDING BUT NOT LIMITED TO: INSULATION, VAPOR BARRIER, VALVES, CAPS, ETC	
6.	SUBMIT SHOP DRAWINGS OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES OR ITEMS ORDERED	
7.	COORDINATE ALL EQUIPMENT REQUIREMENTS WITH APPROPRIATE TRADES (I.E., CONDENSATE PUMPS COORDINATED WITH ELECTRICAL, PLUMBING, ATC, ETC.)	
8.	VERIFY AND COORDINATE ALL EQUIPMENT ACCESS AND CLEARANCES WITH THE ARCHITECT, GENERAL CONTRACTOR, AND/OR CONSTRUCTION MANAGER.	
9.	LOCATE ALL DUCT VOLUME DAMPERS ABOVE ACCESSIBLE LOCATIONS. PROVIDE REMOTE CABLE OPERATED VOLUME DAMPERS WITH THE OPERATOR ACCESSIBLE VIA THE AIR OUTLET WHEN BRANCH DUCTWORK IS LOCATED WITHIN AN INACCESSIBLE LOCATION	
10.	ALL EXPOSED DUCTWORK SHALL BE INTERNALLY LINED, SEE SPECIFICATIONS	
11.	CONTRACTOR SHALL BE RESPONSIBLE FOR THE WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF SAME WHICH MAY BE DAMAGED, LOST OR STOLEN WITHOUT ADDITIONAL COST TO OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING OR REPAIRING ANY BUILDING SYSTEM THAT SERVES OTHER AREAS THAT ARE DAMAGED OR IMPROPERLY MOVED AS A RESULT OF THE WORK.	
12.	BALANCE ALL AIR OUTLETS TO THE CFM INDICATED ON THE PLANS	
13.	ALL CONNECTIONS TO SUPPLY DUCTS AND CEILING DIFFUSERS SHALL BE AIR TIGHT AND SEALED WITH WATER BASED SEALANT	
14.	ALL DUCT SIZES NOTED INDICATE THE CLEAR INSIDE DIMENSIONS OF DUCTWORK. SHEET METAL DIMENSIONS SHALL BE INCREASED WHERE DUCTWORK IS LINED INTERNALLY	
15.	PROVIDE ALL REMOVABLE ACCESS TILES IN HUNG CEILING FOR ACCESS TO ALL VOLUME AND FIRE DAMPERS (EXISTING OR NEW) AND ALL OTHER MECHANICAL AND ELECTRICAL EQUIPMENT REQUIRING ACCESS FOR MAINTENANCE AND ADJUSTMENTS	
16.	LOCATE THERMOSTATS AS REQUIRED AND DICTATED BY THE CONSTRUCTION CONDITIONS	
17.	ALL SUPPLY, RETURN, AND EXHAUST DUCTWORK SHALL BE INSULATED THROUGHOUT. ALL DUCTWORK LOCATED OUTDOORS, ON ROOF SHALL BE INSULATED AND FURTHER WEATHERPROOFED WITH JACKETING	

MECHANICAL CODES AND STANDARDS	
DESIGN AND PERFORMANCE OF COMPONENTS AND METHODS SPECIFIED HEREIN SHALL COMPLY WITH THE APPLICABLE PROVISIONS OF THE CODES, STANDARDS, AND MANUFACTURER'S RECOMMENDATIONS OF THE ENTITIES LISTED BELOW.	
1) BUILDING	FACILITY MANAGEMENT STANDARDS FOR ALTERATIONS AND CONSTRUCTION
2) BC	2018 NORTH CAROLINA BUILDING CODE
3) MC	2018 NORTH CAROLINA MECHANICAL CODE
4) ECC	2018 NORTH CAROLINA ENERGY CONSERVATION CODE
5) ASHRAE	AMERICAN SOCIETY OF HEATING, REFRIGERATION AND AIR CONDITIONING ENGINEERS
6) ASTM	AMERICAN SOCIETY FOR TESTING MATERIALS
7) ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
8) UL	UNDERWRITERS LABORATORIES, INC
9) FM	FACTORY MUTUAL
10) NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
11) SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTOR'S NATIONAL ASSOCIATION
12) ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS
13) AMCA	AIR MOVING AND CONDITIONING ASSOCIATION
14) ARI	AMERICAN REFRIGERATION INSTITUTE
15) MSS	MANUFACTURER'S STANDARDIZATION SOCIETY OF THE VALVE AND FITTING INDUSTRY.


MECHANICAL GENERAL NOTES	
1.	DESIGN DRAWINGS ARE TO BE CONSIDERED DIAGRAMMATIC. OFFSETS MAY BE REQUIRED TO AVOID EXISTING SERVICES, OTHER TRADES, ETC. COORDINATE WORK WITH ALL TRADES AND FIELD CONDITIONS
2.	CX SERVICES TO BE RETAINED BY DTCC
3.	ALL LAB EXHAUST DUCTS SHALL BE CONSTRUCTED OF APPROVED G90 GALVANIZED SHEET STEEL WITH MINIMUM 14 GAGE (0.079 INCHES THICKNESS), UNLESS OTHERWISE SPECIFIED. ALL FUME HOOD EXHAUST DUCTWORK SHALL BE MINIMUM 18 GAUGE WELDED STAINLESS STEEL FROM THE FUME HOOD TO THE MAIN EXHAUST DUCT
4.	LOCATIONS OF NEW UTILITIES ARE GENERALLY SCHEMATIC. CONTRACTOR SHALL COORDINATE ALL NEW UTILITIES, SERVICES, ETC. WITH EXISTING STRUCTURAL AND ARCHITECTURAL DRAWINGS AND PROVIDE ALL OFFSETS AS REQUIRED
5.	CONTRACTOR IS RESPONSIBLE FOR MAINTAINING AND RESTORING THE CONTINUITY OF ALL EXISTING SYSTEMS AFFECTED, INCLUDING BUT NOT LIMITED TO: INSULATION, VAPOR BARRIER, VALVES, CAPS, ETC
6.	SUBMIT SHOP DRAWINGS OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES OR ITEMS ORDERED
7.	COORDINATE ALL EQUIPMENT REQUIREMENTS WITH APPROPRIATE TRADES (I.E., CONDENSATE PUMPS COORDINATED WITH ELECTRICAL, PLUMBING, ATC, ETC.)
8.	VERIFY AND COORDINATE ALL EQUIPMENT ACCESS AND CLEARANCES WITH THE ARCHITECT, GENERAL CONTRACTOR, AND/OR CONSTRUCTION MANAGER.
9.	LOCATE ALL DUCT VOLUME DAMPERS ABOVE ACCESSIBLE LOCATIONS. PROVIDE REMOTE CABLE OPERATED VOLUME DAMPERS WITH THE OPERATOR ACCESSIBLE VIA THE AIR OUTLET WHEN BRANCH DUCTWORK IS LOCATED WITHIN AN INACCESSIBLE LOCATION
10.	ALL EXPOSED DUCTWORK SHALL BE INTERNALLY LINED, SEE SPECIFICATIONS
11.	CONTRACTOR SHALL BE RESPONSIBLE FOR THE WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF SAME WHICH MAY BE DAMAGED, LOST OR STOLEN WITHOUT ADDITIONAL COST TO OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING OR REPAIRING ANY BUILDING SYSTEM THAT SERVES OTHER AREAS THAT ARE DAMAGED OR IMPROPERLY MOVED AS A RESULT OF THE WORK.
12.	BALANCE ALL AIR OUTLETS TO THE CFM INDICATED ON THE PLANS
13.	ALL CONNECTIONS TO SUPPLY DUCTS AND CEILING DIFFUSERS SHALL BE AIR TIGHT AND SEALED WITH WATER BASED SEALANT
14.	ALL DUCT SIZES NOTED INDICATE THE CLEAR INSIDE DIMENSIONS OF DUCTWORK. SHEET METAL DIMENSIONS SHALL BE INCREASED WHERE DUCTWORK IS LINED INTERNALLY
15.	PROVIDE ALL REMOVABLE ACCESS TILES IN HUNG CEILING FOR ACCESS TO ALL VOLUME AND FIRE DAMPERS (EXISTING OR NEW) AND ALL OTHER MECHANICAL AND ELECTRICAL EQUIPMENT REQUIRING ACCESS FOR MAINTENANCE AND ADJUSTMENTS
16.	LOCATE THERMOSTATS AS REQUIRED AND DICTATED BY THE CONSTRUCTION CONDITIONS
17.	ALL SUPPLY, RETURN, AND EXHAUST DUCTWORK SHALL BE INSULATED THROUGHOUT. ALL DUCTWORK LOCATED OUTDOORS, ON ROOF SHALL BE INSULATED AND FURTHER WEATHERPROOFED WITH JACKETING

MECHANICAL CODES AND STANDARDS	
DESIGN AND PERFORMANCE OF COMPONENTS AND METHODS SPECIFIED HEREIN SHALL COMPLY WITH THE APPLICABLE PROVISIONS OF THE CODES, STANDARDS, AND MANUFACTURER'S RECOMMENDATIONS OF THE ENTITIES LISTED BELOW.	
1) BUILDING	FACILITY MANAGEMENT STANDARDS FOR ALTERATIONS AND CONSTRUCTION
2) BC	2018 NORTH CAROLINA BUILDING CODE
3) MC	2018 NORTH CAROLINA MECHANICAL CODE
4) ECC	2018 NORTH CAROLINA ENERGY CONSERVATION CODE
5) ASHRAE	AMERICAN SOCIETY OF HEATING, REFRIGERATION AND AIR CONDITIONING ENGINEERS
6) ASTM	AMERICAN SOCIETY FOR TESTING MATERIALS
7) ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
8) UL	UNDERWRITERS LABORATORIES, INC
9) FM	FACTORY MUTUAL
10) NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
11) SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTOR'S NATIONAL ASSOCIATION
12) ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS
13) AMCA	AIR MOVING AND CONDITIONING ASSOCIATION
14) ARI	AMERICAN REFRIGERATION INSTITUTE
15) MSS	MANUFACTURER'S STANDARDIZATION SOCIETY OF THE VALVE AND FITTING INDUSTRY.

MECHANICAL GENERAL NOTES	
1.	DESIGN DRAWINGS ARE TO BE CONSIDERED DIAGRAMMATIC. OFFSETS MAY BE REQUIRED TO AVOID EXISTING SERVICES, OTHER TRADES, ETC. COORDINATE WORK WITH ALL TRADES AND FIELD CONDITIONS
2.	CX SERVICES TO BE RETAINED BY DTCC
3.	ALL LAB EXHAUST DUCTS SHALL BE CONSTRUCTED OF APPROVED G90 GALVANIZED SHEET STEEL WITH MINIMUM 14 GAGE (0.079 INCHES THICKNESS), UNLESS OTHERWISE SPECIFIED. ALL FUME HOOD EXHAUST DUCTWORK SHALL BE MINIMUM 18 GAUGE WELDED STAINLESS STEEL FROM THE FUME HOOD TO THE MAIN EXHAUST DUCT
4.	LOCATIONS OF NEW UTILITIES ARE GENERALLY SCHEMATIC. CONTRACTOR SHALL COORDINATE ALL NEW UTILITIES, SERVICES, ETC. WITH EXISTING STRUCTURAL AND ARCHITECTURAL DRAWINGS AND PROVIDE ALL OFFSETS AS REQUIRED
5.	CONTRACTOR IS RESPONSIBLE FOR MAINTAINING AND RESTORING THE CONTINUITY OF ALL EXISTING SYSTEMS AFFECTED, INCLUDING BUT NOT LIMITED TO: INSULATION, VAPOR BARRIER, VALVES, CAPS, ETC
6.	SUBMIT SHOP DRAWINGS OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES OR ITEMS ORDERED
7.	COORDINATE ALL EQUIPMENT REQUIREMENTS WITH APPROPRIATE TRADES (I.E., CONDENSATE PUMPS COORDINATED WITH ELECTRICAL, PLUMBING, ATC, ETC.)
8.	VERIFY AND COORDINATE ALL EQUIPMENT ACCESS AND CLEARANCES WITH THE ARCHITECT, GENERAL CONTRACTOR, AND/OR CONSTRUCTION MANAGER.
9.	LOCATE ALL DUCT VOLUME DAMPERS ABOVE ACCESSIBLE LOCATIONS. PROVIDE REMOTE CABLE OPERATED VOLUME DAMPERS WITH THE OPERATOR ACCESSIBLE VIA THE AIR OUTLET WHEN BRANCH DUCTWORK IS LOCATED WITHIN AN INACCESSIBLE LOCATION
10.	ALL EXPOSED DUCTWORK SHALL BE INTERNALLY LINED, SEE SPECIFICATIONS
11.	CONTRACTOR SHALL BE RESPONSIBLE FOR THE WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF SAME WHICH MAY BE DAMAGED, LOST OR STOLEN WITHOUT ADDITIONAL COST TO OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING OR REPAIRING ANY BUILDING SYSTEM THAT SERVES OTHER AREAS THAT ARE DAMAGED OR IMPROPERLY MOVED AS A RESULT OF THE WORK.
12.	BALANCE ALL AIR OUTLETS TO THE CFM INDICATED ON THE PLANS
13.	ALL CONNECTIONS TO SUPPLY DUCTS AND CEILING DIFFUSERS SHALL BE AIR TIGHT AND SEALED WITH WATER BASED SEALANT
14.	ALL DUCT SIZES NOTED INDICATE THE CLEAR INSIDE DIMENSIONS OF DUCTWORK. SHEET METAL DIMENSIONS SHALL BE INCREASED WHERE DUCTWORK IS LINED INTERNALLY
15.	PROVIDE ALL REMOVABLE ACCESS TILES IN HUNG CEILING FOR ACCESS TO ALL VOLUME AND FIRE DAMPERS (EXISTING OR NEW) AND ALL OTHER MECHANICAL AND ELECTRICAL EQUIPMENT REQUIRING ACCESS FOR MAINTENANCE AND ADJUSTMENTS
16.	LOCATE THERMOSTATS AS REQUIRED AND DICTATED BY THE CONSTRUCTION CONDITIONS
17.	ALL SUPPLY, RETURN, AND EXHAUST DUCTWORK SHALL BE INSULATED THROUGHOUT. ALL DUCTWORK LOCATED OUTDOORS, ON ROOF SHALL BE INSULATED AND FURTHER WEATHERPROOFED WITH JACKETING

MECHANICAL CODES AND STANDARDS	
DESIGN AND PERFORMANCE OF COMPONENTS AND METHODS SPECIFIED HEREIN SHALL COMPLY WITH THE APPLICABLE PROVISIONS OF THE CODES, STANDARDS, AND MANUFACTURER'S RECOMMENDATIONS OF THE ENTITIES LISTED BELOW.	
1) BUILDING	FACILITY MANAGEMENT STANDARDS FOR ALTERATIONS AND CONSTRUCTION
2) BC	2018 NORTH CAROLINA BUILDING CODE
3) MC	2018 NORTH CAROLINA MECHANICAL CODE
4) ECC	2018 NORTH CAROLINA ENERGY CONSERVATION CODE
5) ASHRAE	AMERICAN SOCIETY OF HEATING, REFRIGERATION AND AIR CONDITIONING ENGINEERS
6) ASTM	AMERICAN SOCIETY FOR TESTING MATERIALS
7) ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE
8) UL	UNDERWRITERS LABORATORIES, INC
9) FM	FACTORY MUTUAL
10) NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
11) SMACNA	SHEET METAL AND AIR CONDITIONING CONTRACTOR'S NATIONAL ASSOCIATION
12) ASME	AMERICAN SOCIETY OF MECHANICAL ENGINEERS
13) AMCA	AIR MOVING AND CONDITIONING ASSOCIATION
14) ARI	AMERICAN REFRIGERATION INSTITUTE
15) MSS	MANUFACTURER'S STANDARDIZATION SOCIETY OF THE VALVE AND FITTING INDUSTRY.

MECHANICAL GENERAL NOTES	
1.	DESIGN DRAWINGS ARE TO BE CONSIDERED DIAGRAMMATIC. OFFSETS MAY BE REQUIRED TO AVOID EXISTING SERVICES, OTHER TRADES, ETC. COORDINATE WORK WITH ALL TRADES AND FIELD CONDITIONS
2.	CX SERVICES TO BE RETAINED BY DTCC
3.	ALL LAB EXHAUST DUCTS SHALL BE CONSTRUCTED OF APPROVED G90 GALVANIZED SHEET STEEL WITH MINIMUM 14 GAGE (0.079 INCHES THICKNESS), UNLESS OTHERWISE SPECIFIED. ALL FUME HOOD EXHAUST DUCTWORK SHALL BE MINIMUM 18 GAUGE WELDED STAINLESS STEEL FROM THE FUME HOOD TO THE MAIN EXHAUST DUCT
4.	LOCATIONS OF NEW UTILITIES ARE GENERALLY SCHEMATIC. CONTRACTOR SHALL COORDINATE ALL NEW UTILITIES, SERVICES, ETC. WITH EXISTING STRUCTURAL AND ARCHITECTURAL DRAWINGS AND PROVIDE ALL OFFSETS AS REQUIRED
5.	CONTRACTOR IS RESPONSIBLE FOR MAINTAINING AND RESTORING THE CONTINUITY OF ALL EXISTING SYSTEMS AFFECTED, INCLUDING BUT NOT LIMITED TO: INSULATION, VAPOR BARRIER, VALVES, CAPS, ETC
6.	SUBMIT SHOP DRAWINGS OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES OR ITEMS ORDERED
7.	COORDINATE ALL EQUIPMENT REQUIREMENTS WITH APPROPRIATE TRADES (I.E., CONDENSATE PUMPS COORDINATED WITH ELECTRICAL, PLUMBING, ATC, ETC.)
8.	VERIFY AND COORDINATE ALL EQUIPMENT ACCESS AND CLEARANCES WITH THE ARCHITECT, GENERAL CONTRACTOR, AND/OR CONSTRUCTION MANAGER.
9.	LOCATE ALL DUCT VOLUME DAMPERS ABOVE ACCESSIBLE LOCATIONS. PROVIDE REMOTE CABLE OPERATED VOLUME DAMPERS WITH THE OPERATOR ACCESSIBLE VIA THE AIR OUTLET WHEN BRANCH DUCTWORK IS LOCATED WITHIN AN INACCESSIBLE LOCATION
10.	ALL EXPOSED DUCTWORK SHALL BE INTERNALLY LINED, SEE SPECIFICATIONS
11.	CONTRACTOR SHALL BE RESPONSIBLE FOR THE WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF SAME WHICH MAY BE DAMAGED, LOST OR STOLEN WITHOUT ADDITIONAL COST TO OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPLACING OR REPAIRING ANY BUILDING SYSTEM THAT SERVES OTHER AREAS THAT ARE DAMAGED OR IMPROPERLY MOVED AS A RESULT OF THE WORK.
12.	BALANCE ALL AIR OUTLETS TO THE CFM INDICATED ON THE PLANS
13.	ALL CONNECTIONS TO SUPPLY DUCTS AND CEILING DIFFUSERS SHALL BE AIR TIGHT AND SEALED WITH WATER BASED SEALANT
14.	ALL DUCT SIZES NOTED INDICATE THE CLEAR INSIDE DIMENSIONS OF DUCTWORK. SHEET METAL DIMENSIONS SHALL BE INCREASED WHERE DUCTWORK IS LINED INTERNALLY
15.	PROVIDE ALL REMOVABLE ACCESS TILES IN HUNG CEILING FOR ACCESS TO ALL VOLUME AND FIRE DAMPERS (EXISTING OR NEW) AND ALL OTHER MECHANICAL AND ELECTRICAL EQUIPMENT REQUIRING ACCESS FOR MAINTENANCE AND ADJUSTMENTS



1 Mechanical - Roof Level Copy 1  
EP-M202 3/32" = 1'-0"

### GENERAL NOTES

- INTEGRATE ALL EQUIPMENT WITH THE CONTROL SYSTEM.
- ALL EXPOSED EQUIPMENT, PIPING, DUCTWORK, ETC. SHALL BE PAINTED. SEE ARCHITECTURAL PLANS AND SPECIFICATIONS FOR COLORS, FINISH, ETC.
- COORDINATE ACCESS FOR ALL EQUIPMENT, SENSORS, AND DAMPERS WITH ARCHITECTURAL DRAWINGS.
- MECHANICAL CONTRACTOR TO COORDINATE ALL MECHANICAL LAYOUTS FOR DUCTS AND PIPING. ALSO, COORDINATE WITH ARCHITECTURAL DRAWINGS AND OTHER TRADES. SHEET METAL SHOP DRAWINGS AND COORDINATION DRAWINGS MUST BE PRODUCED AND SUBMITTED FOR REVIEW BY ENGINEER AND OWNER FOR APPROVAL PRIOR TO PROCEEDING WITH ANY FABRICATIONS AND INSTALLATIONS.
- ALL DUCTWORK LOCATED OUTDOORS, ON ROOF SHALL BE INSULATED AND FURTHER WEATHERPROOFED WITH JACKETING.

### WALL TYPE LEGEND

	1-HOUR FIRE BARRIER
	2-HOUR FIRE BARRIER

### KEY PLAN

CLIENT AND PROJECT

**DURHAM TECH**

DURHAM TECH COMMUNITY COLLEGE

**LIFE SCIENCES BUILDING**

1650 E Lawson St.  
Durham, NC 27703

SCO ID: 23-26245-02B  
NCCCS ID: 2731

DESIGNER

**AJA+**  
Andre Johnson Architects

PO BOX 14637  
RALEIGH, NORTH CAROLINA 27620  
TELEPHONE: 919.661.6935  
MAIL: info@andrejohnsonarchitect.com

© 2024 Andre Johnson Architect, PLLC  
Duplication or reproduction by any means without the express written consent of Andre Johnson Architect is a violation of Federal and International law. The information contained on this document is the intellectual property of Andre Johnson Architect and all rights thereto are Reserved. For exceptions, refer to the Owner-Architect Agreement.

**O'Brien Atkins**

PO BOX 12037  
RESEARCH TRIANGLE PARK  
NORTH CAROLINA 27709  
TELEPHONE: 919.941.9000  
www.obrienatkins.com

CONSULTANT AND REGISTRATION

**LORING CONSULTING ENGINEERS**

Loring Consulting Engineers, Inc.  
1007 Souter Road, Suite 210  
Durham, NC 27703  
P: 919.355.5000  
www.loringengineers.com  
New York City • Washington, DC • Princeton • Durham • Toronto

REGISTRATION

NC LICENSE: C-3202

05-07-2025

ISSUE



No.	Date	Description
-----	------	-------------

SHEET INFO

**EARLY PACKAGE MECHANICAL ROOF OVERALL PLAN**


PROJECT NO: 13774-000  
DATE: 05/07/2025  
EARLY EQUIPMENT PACKAGE

EP-M202




1 TYPICAL AHU-01 ARRANGEMENT Copy 1  
N.T.S.

2 TYPICAL AHU-02 ARRANGEMENT Copy 1  
N.T.S.




3 TYPICAL AHU-03 ARRANGEMENT Copy 1  
N.T.S.

Operating weight : 15000 lbs



4 HEAT RECOVERY SKID DETAIL Copy 1  
N.T.S.



CLIENT AND PROJECT



DURHAM TECH  
COMMUNITY  
COLLEGE

LIFE SCIENCES  
BUILDING

1650 E Lawson St.  
Durham, NC 27703

SCO ID: 23-26245-02B  
NCCCS ID: 2731

DESIGNER



PO BOX 14637  
RALEIGH, NORTH CAROLINA 27620  
TELEPHONE: 919.661.6935  
MAIL: info@andrejohnsonarchitect.com

© 2024 Andre Johnson Architect, PLLC  
Duplication or reproduction by any means without  
the express written consent of Andre Johnson  
Architect is a violation of Federal and international  
law. The information contained on this document is  
the intellectual property of Andre Johnson Architect  
and all rights thereto are Reserved. For exceptions,  
refer to the Owner-Architect Agreement.



PO BOX 12037  
RESEARCH TRIANGLE PARK  
NORTH CAROLINA 27709  
TELEPHONE: 919.941.9000  
www.obrienatkins.com

CONSULTANT AND REGISTRATION

LORING  
CONSULTING ENGINEERS

Loring Consulting Engineers, Inc.  
3007 Souter Road, Suite 210  
Durham, NC 27703  
P: 919.355.5500  
www.loringengineers.com  
New York City • Washington, DC • Princeton • Durham • Toronto

REGISTRATION



NC LICENSE: C-3202



05-07-2025

ISSUE

No. Date Description

SHEET INFO  
EARLY PACKAGE  
MECHANICAL  
DETAILS IV

EP-M404

PROJECT NO: 13774-000  
DATE: 05/07/2025  
EARLY EQUIPMENT PACKAGE










- RUN-AROUND LOOP PUMP FAILURE: COMMANDED ON, BUT THE STATUS IS OFF.
- RUN-AROUND LOOP PUMP IN HAND: COMMANDED OFF, BUT THE STATUS IS ON.
- RUN-AROUND LOOP PUMP RUNTIME EXCEEDED: STATUS RUNTIME EXCEEDS A USER DEFINABLE LIMIT (ADJ)



SEQUENCE OF OPERATION MUST  
MATCH AND MEET OWNER  
REQUIREMENTS  
CONTROLS SUBMITTAL AND  
CONTROLS SEQUENCE MUST BE  
SUBMITTED TO OWNER AND  
ENGINEER FOR APPROVAL PRIOR  
TO PURCHASING AND  
IMPLEMENTING